

मिति २०८१ माघ ११ गते शुक्रवाको आर्थिक अभियानमा  
प्रकाशित



## INVITATION FOR QUOTATION

Himalayan Distillery Ltd. invites quotation for 'Refrigeration Room & Allied work' from the interested eligible and resourceful National/International Manufacturer/Authorized or Sole Distributor/Firms having sufficient resources & experience in execution of similar type of works as details here under.

The complete set of documents (Scope of Work) can be received at free of cost from its Contact Office at Jawalakhel, Lalitpur or can be downloaded from the website of the company "www.himalayandistillery.com".

Interested company/firm must submit sealed quotation at following address within 7th February, 2025. Proposals received after the deadline will not be considered for further evaluation.

- 1. Project Location:** Soludhudhkunda Municipality-8, Pattale, Solukhumbu, Nepal
- 2. Access road of site:** Connected with Ghurmi-Salleri Highway
- 3. Scope of Work:** Supply, Installation and Commissioning of Machinery and Equipment including insulation material all complete.
- 4. Required Document:**
  - Company Profile with owner's & Key Management Staff's CV and identification documents such as citizenship certificate
  - Notarized copy of PAN/VAT, Company Registration Certificate
  - Latest Tax Clearance Certificate
- 5. Eligibility Criteria:**
  - **Experience:** Successful completion certificate.

Further information can be obtained from office of the company at Jawalakhel, Lalitpur, Nepal.



## Himalayan Distillery Ltd.

Contact Office, Uttar Bagaicha Marg, Jawalakhel, Lalitpur, Nepal  
Contact No.: 01-5427465

*'Himalayan Distillery Limited, reserves all the rights to accept or reject any or all the quotations fully or partially without assigning any reason whatsoever and is not bound to accept the lowest quotation.'*

**HIMALAYAN DISTILLERY LTD.**  
**Birgunj, Parsa**

<b>Specifications</b>	
<b>Refrigeration room (Cold Room)</b>	
<b>Dimension (coldroom)</b>	approx. 25 m x 20 m x 6 m
<b>Anteroom</b>	Yes
<b>Specification</b>	120 mm Panel
<b>Panel Thickness - Wall and Ceiling</b>	120 mm PUF with density of 40+/-2 kg/m <sup>3</sup>
	100 mm PUF for trangular part of side wall
	50 mm PUF for extended part of side wall
<b>Panel Surface Materials</b>	Interlocking Panels; Both sides PPGI sheet thickness 0.45mm
<b>Thermal Conductivity (K-Factor)</b>	0.22 W/m-K
<b>U-Factor (Heat Transfer Coefficient)</b>	0.018 – 0.022 W/m <sup>2</sup> K
<b>Fire Resistance</b>	Self-extinguishing per ASTM D 1692
<b>Water Absorption</b>	< 1% w/v
<b>Closed Cell Content</b>	≥ 97%
<b>Compressive Strength</b>	2.0 – 2.6 kg/cm <sup>2</sup>
<b>Internal Finish</b>	Pre-painted GI Sheet
<b>External Finish</b>	Pre-painted GI Sheet
<b>Floor Panel Thickness</b>	50 mm PUF with Bitumen and Tarfelt
<b>Locking (Wall-Floor Panel)</b>	Reinforced U-profile locking
<b>Locking (Wall-Ceiling Panel)</b>	Flashing
<b>Corner Sealing (Inside)</b>	Coving on all columns
<b>Edge and Corner Sealing</b>	Standard edge seals
<b>Digital Temperature Control</b>	Included
<b>Door (anteroom)</b>	2.4 m L x 2.75 m (H) - Swing doble leaf refrigerated door with provision of magnetic access control lock
<b>Door (coldroom)</b>	2.4 m L x 2.75 m (H) - Sliding refrigerated door with provision of magnetic access control lock
<b>Refrigeration System of capacity 4 kW, R407C, suitable for (+)15 deg C Room Temperature, with hermetic compressor, air-cooled condensing unit, evaporator, and required inter-connecting piping as per layout</b>	4 sets
<b>Heater 5kW</b>	4 sets
<b>Temperature Control</b>	Microprocessor based with Temperature Indicator-cum-controller for both cooling and heating system
<b>Lighting</b>	LED Flame Proof for 50 Lux
<b>Humidifier</b>	3 nos. 2W + 1S
<b>Power Supply</b>	415V, 50 Hz, 3 Ph

Please include the following information in your quotation:

1. Rate per Unit and total cost
2. Payment terms
3. Incoterms
4. HS Code
5. Delivery or lead time
6. Warranty or service terms (if applicable)

Note: Please also have a look on below things, while preparing the quotation of Puff Panel: Periphery wall (side wall) including triangular part, floor's puff panel and extended part of side wall to be included.